

M-POS 160-AS UV400

(非球面設計)

度数 (\rightarrow)	S TC (-)															
	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00
0.00																
0.25																
0.50																
0.75																
1.00																
1.25																
1.50																
1.75																
2.00							75									
2.25																
2.50																
2.75																
3.00																
3.25																
3.50																
3.75																
4.00																
4.25																
4.50																
4.75																
5.00																
5.25																
5.50																
5.75																
6.00																
6.25																
6.50																
6.75																
7.00							70									
7.25																
7.50																
7.75																
8.00																

度数 (\rightarrow)	S TC (+)															
	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00
0.00	×															
0.25																
0.50																
0.75																
1.00																
1.25																
1.50																
1.75																
2.00																
2.25																
2.50																
2.75																
3.00																
3.25																
3.50																
3.75																
4.00																
4.25																
4.50																
4.75																
5.00																
5.25																
5.50																
5.75																
6.00																

混合乱視

度数 (\rightarrow)	TC (-)											
	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00
0.25												
0.50												
0.75												
1.00												
1.25												
1.50												
1.75												
2.00												
2.25												
2.50												
2.75												
3.00												

1、色塗り範囲は、工場在庫範囲

2、他範囲は、特注研磨品範囲



レンズ梱包仕様



仕 様	
設 計	非球面設計
屈折率	1.60
比 重	1.30
アツペ数	42
紫外線カット	UV400
コート	超撥水コート

カラー加工	
<input type="radio"/> アリアーテトレスカラー	
<input type="radio"/> M-POSオリジナルカラー	
<input type="radio"/> 見本染色 不可	

研磨加工	
偏 心	不 可
プリズム	3△まで可
外径指定	1mm単位/ 最小55mm
厚み指定	可